

12-04-85

D. Butlers
T. Wood

T5N RIW

T@ 23M (used for 23/24)

| | | | | |
|-----|------|---------------|------|--|
| 23Q | D | 0° 00' 09" | 05 | |
| | R | 180 00 01 | | |
| 23N | D | 96 05 20 | 15 | |
| | R | 276 05 10 | | |
| | M | = 96 05 10 | | |
| 23Q | D | 90 05 40 | 34.5 | |
| | R | 270 05 29 | | |
| 23N | D | 186 10 52 | 45 | |
| | R | 06 10 38 | | |
| | M | = 96 05 10.5 | | |
| | F.M | = 96 05 10. | | |
| 23N | D | 0 00 12 | 09.5 | |
| | R | 180 00 07 | | |
| 23L | D | 171 35 43 | 38 | |
| | R | 351 35 33 | | |
| | M | = 171 35 28.5 | | |
| 23N | D | 90 05 41 | 34 | |
| | R | 270 05 27 | | |
| 23L | D | 261 41 03 | 58 | |
| | R | 81 40 53 | | |
| | M | = 171 35 24 | | |
| | F.M | = 171 35 26.2 | | |
| 23L | D | 0 00 09 | 04.5 | |
| | R | 180 00 00 | | |
| 23Q | D | 92 19 31 | 26.5 | |
| | R | 272 19 22 | | |
| | M | = 92 19 22 | | |
| 23L | D | 90 05 38 | 30.5 | |
| | R | 270 05 23 | | |
| 23Q | D | 182 24 55 | 50.5 | |
| | R | 02 24 46 | | |
| | M | = 92 19 20 | | |
| | F.M. | = 92 19 21 | | |

T. Wood = 359 59 57

Cont. Next pg.