

*
W

T @ 9' E CONT

9 16	D	90-05-40	39.5'	
	R	270-05-39		
9" D"	D	91-12-24	22'	
	R	271-12-20		
	M	1-06-42.5'		1-06-42.5
	Fm	1-06-42.00'		X

9" D"	D	0-00-09	06'	
	R	180-00-03		

1/4 COR MON 10 15	D	178-37-24	24.5'	
	R	358-37-25		
	M	178-37-18.5'		

9" D"	D	90-05-46	44'	
	R	270-05-42		

10 15	D	268-43-06	05.5'	
	R	88-43-05		
	M	178-37-21.5'		

10 15	Fm	178-37-20.00'		X
	D	0-00-08	07.5'	

RR spike @ 16/15	R	180-00-07		
	D	88-44-52	50.5'	

RR spike @ 16/15	R	268-44-49		
	M	88-44-43'		

10 15	D	90-05-41	43.5'	
	R	270-05-46		

RR spike @ 16/15	D	178-50-29	28'	
	R	358-50-27		

RR spike @ 16/15	M	88-44-44.5'		
	Fm	88-44-43.75'		X

Dist to RR spike @ 16/15 = 2661.82

" " 1/4 COR MON 9/16 = 2523.95

" " 9" D = 3175.60

" " 1/4 COR MON 10/15 = 2694.02