

*	22 "B"			
S	22 "A"	D	0 00 12	14.5 ✓
		R	180 00 21	
W	21 "B"	D	38 08 25	29 ✓
		R	218 08 33	
		M	38 08 12.5	✓
	22 "A"	D	90 05 40	42.5 ✓
		R	270 05 47	
	21 "B"	D	128 13 54	54 ✓
		R	308 13 54	
		M	38 08 10.5	✓
		FM	38 08 11.5	✓ X
W	21 "B"	D	0 00 10	15 ✓
		R	180 00 20	
N RR spike @ 16/15		D	140 02 34	32.5 ✓
		R	320 02 31	
		M	140 02 17.5	✓
	21 "B"	D	90-05-42	43.5 ✓
		R	270-05-45	
RR spike		D	230-08-05	06.5 ✓
		R	50-08-08	
		M	140-02-23	✓
		FM	140-02-20.25	✓ X
N RR spike		D	0-00-07	05.5 ✓
		R	180-00-04	
E	15 "A"	D	72-08-55	56 ✓
		R	252-08-57	
		M	72-08-50.5	✓
RR spike		D	90-05-42	41.5 ✓
		R	270-05-41	
	15 "A"	D	162-14-33	35.5 ✓
		R	342-14-38	
		M	72-08-54	✓
		FM	72-08-52.25	✓ X

38-08-11.0

140-02-19.50

72-08-51.50