

7 @ 2.0 CONT.

20 B	D	0	00	10	9✓	
	R	180	00	08		
20 E	D	75°	18	15	11.5✓	
	R	255°	18	08		
	M	75°	18	02.25	02.5"	
20 B	D	90°	05	40"	38✓	
	R	270	05	36		
20 E	D	165°	23	42	40✓	
	R	345°	23	38		
	M	75°	18	02"		
	FM	75°	18	02.125	2.25" (02)	
20 E	D	0	00	10	11✓	
	R	180	00	12		
20 G	D	94	35	13	12✓	
	R	274	35	11		
	M	94	35	01✓		
20 E	D	90	05	40	39✓	
	R	270	05	38		
20 G	D	184	40	44	43✓	
	R	04	40	42		
	M	94	35	04✓		
	FM	94	35	02.5	✓ (02)	
20 G	D	0°	00	10	12.5✓	
	R	180°	00	15"		
29 G	D	92°	15'	49"	49.5✓	
	R	272°	15	50"		
	M	92°	15"	37✓		
20 G	D	90	05	45	46.5✓	
	R	270	05	48		
29 G	D	182°	21	22	23	
	R	02	21	24		
	M	92	15	36.5✓		
	FM	92	15	36.75	(37)	

(75-18-02.25) * * *

(94-35-02.50) * * *

(92-15-36.75) * * *