

Cont.

T@ 28B

27A	D	90	05	40	44.5V	
	R	270	05	49		
27B	D	126	14	00	05.5V	22.75
	R	306	14	11		(36-08-22.75)*
	M	36°	08	21V		22.75*
	F.M.	36°	08	23.75	(18)	22.75

27B	D	0	00	12	15.5V	
	R	180	00	19		

28A	D	253	54	33	38V	
	R	573	54	43		
	M	253°	54	22.5V	22.5	

27B	D	90	05	41	44.5V	
	R	270	05	48		

28A	D	344	00	00	0.3V	253-54-28.50*
	R	164	00	06		19.50*
	M	253°	54	18.5V	18.5	
	F.M.	253°	54	20.5"	(19)	19.5

Dist to 27B 2113.11  
 Dist to 27A 1413.93  
 Dist to 28A 635.38

Φ 10-7-87

T@ 27B

28B	D	0	00	11"	23.5V	
	R	180	00	36"		

1/16 34	D	227	36	19"	31.5V	
	R	47	36	44"		
	M	227°	36	08V		

28B	D	90°	05'	40"	50V	
	R	270°	06'	00"		

1/16 34	D	317°	41'	43"	54V	227-36-06.00**
	R	137°	42'	05"		
	M	227°	36'	04V		

F.M. 227° 36' 06"

Dist to 1/16 = 965.52  
 Dist to 28B = 2113.08

