

cont.

4-25 85

✓

X @ 3.2

32G	D	0° 00'	10"	60.5"
	R	180° 00'	05"	07.5"
32I	D	79° 35'	03"	00"
	R	259° 34'	57"	
	M=	79° 34'	52.5"	
32G	D	90° 05'	40"	37
	R	270° 05'	34"	
32I	D	169° 40'	34"	32"
	R	349° 40'	30"	
	M=	79° 34'	55"	
	F.M=	79° 34'	53.75"	
32I	D	0° 00'	11"	11"
	R	180° 00'	11"	
32A	D	94° 01'	23"	22.5
	R	274° 01'	22"	
	M=	94° 01'	11.5"	
32I	D	90° 05'	42"	42"
	R	270° 05'	42"	
32A	D	184° 06'	48"	49
	R	04° 06'	50	
	M=	94° 01'	07"	
	F.M=	94° 01'	09.25"	
32A	D	0° 00'	09	08.5
	R	180° 00'	08	
31/32	D	96° 53'	54"	53.5
2" Alum. Pipe	R	276° 53'	53"	
	M=	96° 53'	45"	
32A	D	90° 05'	41"	38.5"
	R	270° 05'	36"	
31/32	D	186° 59'	23"	22"
2" pipe	R	06° 59'	21"	
	M=	96° 53'	43.5"	
	F.M=	96° 53'	47.25"	

cont.