

$\pi @ 2''$  Alum. Pipe

$\frac{28}{33}$

$\frac{29}{33} | \frac{27}{34}$

D	0° 00' 11"	18
R	180° 00' 25"	
D	180° 38' 27"	28.5
R	0° 38' 30"	
M	180 38 10.5	

$\frac{28}{33} | \frac{27}{34}$

33B

D	90 05 40	41
R	270 05 42	
D	270 43 45	49.5
R	90 43 54	
M	180 38 8.5	
F.M	180 38 9.5	

Dist to  $\frac{29}{33} | \frac{27}{34} = 2657.36$

Dist to  $\frac{28}{33} | \frac{27}{34} = 2446.22$  //

$\pi @ 2''$  Alum. Pipe for  $\frac{28}{33}$  B.S.  $\frac{28157}{33134} @ 0° 00' 00''$

\* RT 88° 41' 43" Dist. 670.30 to R.R. spike on 2700N.

$\pi @ 33B$

28E	D	0° 00' 10"	13.5"
	R	180° 00' 17"	
$\frac{26}{33}$ 2" pipe	D	80° 00' 25"	28
	R	260 00 31	
	M	80 00 14.5	

28E	D	90 05 40	41.5
	R	270 05 43	

$\frac{26}{33}$ 2" pipe	D	170 05 50	55.5
	R	350 06 01	
	M	0 05 14	

F.M 80-00-14.25

Dist to 2" pipe = 2446.16