

Seventh Standard Parallel South - through R. 9. W.

Beg. at cor. Tp. 35. S. R. 9. W. on 7th St. Par.

From which I ran E. on S. side, Sec 31, Va. 11.10 E.

4.00 Low timber, bears NWS, paper thin ridge N.E.

15.00 Hollow, 100 ft. below ridge, drains S.E. to Summit Cr.

27.00 Ridge slopes S.E. to Cañon.

46.00 Set sand stone 14 x 15 - 9' in ground for 10' on N. side
N. side - Q.A. 5' di 44° E 60 lbs. dip of bed + rock

44.00 Enter timber along creek bottom.

47.00 Summit Cr. 25 lbs. N.E. heads S.E. over flows

53.50 Branch of Summit Cr. NW to main Cr. heads 2.5' S.E.

80. Set Sand Stone 20 x 9 x 5.15' in ground, under

For cor. to Sec 21-22, on 7th St. Par. is pine 24' di
bears 58° E S. abs. sand rolling. Two trees above

E. along S. side, Sec 32.

7.00 Enter timber, NWS.

40. Set Vol. Stone 14 x 10' in ground for 10' on N. side
Across 4' 50° E 8 lbs. dip, with near N.W.

41. creek runs N.W.

46.75 15' N.W.

52.00 30' S.E.