

STA	± EL	+	H1	DIST RT - ROD	
8+64 ✓				<u>21 ± CUL</u> 18" CONC 13.20	69.27
8+50 ✓				<u>5 ± OR</u> 12.29	70.18
8+35 <sup>92</sup> ✓ PC	4668.86	13.61	4682.47	<u>5 ± OIL</u> 13.44	69.03
8+00 ✓				<u>5 ± OIL</u> 3.92	66.38
7+50 ✓				<u>6 ± OIL</u> 7.28	63.02
7+45 ✓				<u>26 CR &amp; PT</u> 8.5	61.80
7+33 ✓				<u>43' CR INT</u> 9.3	61.00
7+00 ✓	4659.20	11.10	70.30	<u>6 ± OIL</u> 71.04	59.26
6+89 ✓				<u>29 ± CUL</u> 30" CONC 5.76	56.68
6+50 ✓				<u>4 ± OIL</u> 6.84	55.60
6+38 ✓ PC				<u>4 ± OIL</u> 7.66	54.78
6+00 ✓				<u>5 ± OIL</u> 10.74	51.70
5+59 ✓				<u>27 ± CUL</u> 30" CONC 15.55	46.89
5+50 ✓	4647.62	14.82	4662.44	<u>6 ± OIL</u> 14.63	47.81
5+06 ✓				<u>26 ± 18" CONC CUL</u> 7.7	41.74
5+00 ✓				<u>6 ± OIL</u> 5.47	43.97
4+91 ✓				<u>26 ± 18" CONC CUL</u> 8.06	41.38
4+82 ✓				<u>26 ± CR @ 3' FALLS</u> 8.08	41.36
4+50 ✓	4640.24	9.20	4649.44	<u>7 ± OIL</u> 9.07	40.37
4+19 ✓				<u>25 ± CUL</u> 2.2	35.71