

Bearing	+	H.I.	-	ELEV	DIST
0° 00'	10.26	864.75		4854.49	156'
353° 20'			9.2	865.5	92'
307° 30'			5.3	859.45	46'
288° 45'			4.7	860.05	101'
344° 35'			6.18	858.5	27'
297° 15'			4.86	859.7	32'
301° 14'			7.25	857.5	101'
252° 26'			4.82	859.8	23'
220° 0'			2.3	862.4	
176° 55'			0.72	864.03	57'
250°					
Σ #1		H.I.	4.65	860.10	
192° 10'					112'
Σ 2	11.1	871.2	4.7	65.9	12.5
321° 06'			8.65	62.6	95'
			5.7	65.5	10'
271° 45'			5.0	66.2	20'
260° 15'			1.5	69.7	98'
259° 0'			0.1	71.1	140'
144° 94'			1.3	69.9	26'
276° 45'			7.0	64.2	62'
280° 35'			7.0	64.2	24'
# 3	9.1	875.0	8.5	870.7	42'
170° 30'			0.1	869.7	40'
103° 50'			5.3	869.7	29'
77° 55'			6.0	869.0	80'
		864.7	7.2	857.5	412'
FP			2.6	62.1	66'
	10.5	672.6			