

Lt.

Row	D:	<u>C</u>	W.S4	WED	EED	Sh	D:	Row
92.26	92.20	96.54	98.17	98.26	96.50	96.27	94.04	96.34
33	20.4	6.00	18.7	23.0	46.1	50.0	63.6	79
8.94	11.0	6.66	5.03	4.94	6.70	6.93	9.16	6.86

T.P. at 7400 Enail 3.99

B.S. Sta 4150 E 97.15

Lt.

R.

91.5	6.10	94.14	H.I.	103.25				94.4
Top D:								D:
42.5	39.7	97.38	98.16	E.O	98.57	E.O	96.53	340.58
		12.3	6.50	16.9	40.0		22.2	53.0
12.1	9.11	5.87	5.09	4.68	6.72	6.67	9.11	

96.83		98.99	98.93	97.27	97.16	93.91
Slope Lt.		E.O	E.O	Sh	D:	
34	7400	6.0	30.3	3.3	48	
6.42	4.26	4.32	5.98	6.09	9.34	

96.54	96.77	98.69	E.O 99.21	E.O	Sh	D:
26.0	17.2	80K	7450	23	26.4	94.18
6.71	6.48	16.7	4.04	5.48	5.64	37.5
		4.56				9.07

97.89	80K	E.O	98.40	E.O	Sh	D:
21.2	92.22	99.45	8400	98.27	98.16	94.15
5.36	13.2	6.0	3.85	17.8	22	32.8
	4.03	3.80	4.98	5.15	9.10	

E.O	99.69	E.O	Sh	R.O.W
99.79	8450	98.93	98.78	97.59
10.3	13.7	18.0	35.3	
3.46	3.56	4.32	4.38	5.66

100.20	100.04	99.55	99.60	94.64
E.O	9400	E.O	Sh	D:
12.0	12	19	26	
3.05	3.21	3.70	3.65	8.61