



Points for
Masonry in
South Abut
Ogden River Bridge

3" instead of 4" on $\frac{1}{2}$
of no abt being 1"
farther south than
staked out,

A. M.

Oct 18, 90

Linear Feet in and Location of each Pile 72
No Abut Ogden Riv Bridge

	0	1	2
1	0	0	0
2	0	0	0
3	0	0	0
4	0	0	0
5	0	0	0
6	0	0	0
7	0	0	0
8	0	0	0
9	0	0	0
10	0	0	0
11	0	0	0
12	0	0	0
13	0	0	0
14	0	0	0
15	0	0	0
16	0	0	0
17	0	0	0
18	0	0	0
19	0	0	0
20	0	0	0
21	0	0	0
22	0	0	0
23	0	0	0
24	0	0	0
25	0	0	0
26	0	0	0
27	0	0	0
28	0	0	0
29	0	0	0
30	0	0	0
31	0	0	0
32	0	0	0
33	0	0	0
34	0	0	0
35	0	0	0
36	0	0	0
37	0	0	0
38	0	0	0
39	0	0	0
40	0	0	0
41	0	0	0
42	0	0	0
43	0	0	0
44	0	0	0
45	0	0	0
46	0	0	0
47	0	0	0
48	0	0	0
49	0	0	0
50	0	0	0

223 1/2
50 depth holes 7/8" 2-6" long = 223 1/2

Concrete block below pile heads
and flush with top of caps,
and between cap. - Area
same as clearing.

No of Piles	Length	Depth	Volume	Weight
1	15.0	37	11.0	19
2	13.0	38	14.8	20
3	13.0	39	14.4	21
4	15.0	40	13.6	22
5	14.6	41	15.8	23
6	16.0	42	15.8	24
7	15.6	43	16.5	25
8	16.0	44	15.5	26
9	14.6	45	16.0	27
10	14.0	46	14.0	28
11	15.5	47	14.0	29
12	14.0	48	14.0	30
13	13.0	49	14.0	31
14	12.5	50	13.0	32
15	16.5	Total	13.5	33
16	15.4	Total	16.0	34
17	14.5	Total	14.0	35
18	15.7	Total	13.5	36
		Total	732.0 ft	