

Sta	Grading		Station		Wgs		H ¹	Setting of grade line		
	Red	Grade	Rate		E.	W.		Grade	Dist	Prod
107+47 ⁴		62.465	Rate 0.15		107+03.92	106+84.82	4395.17	62.465		
+43 ⁹		.015								
		24925			106+66.92	106+40.92		82.48	10.0	2.10 ⁹
		.250			106+29.27	106+10.57				
106+93 ⁸²		25829						82.53	10.0	2.10 ⁸
		.3512								
106+43 ⁷¹		29831						82.80	10.00	2.19
		.1493								
105+98 ⁹		32324			105+91.5	105+73.1		83.23	10.0	1.90
		.2523			105+54.2		4395.56			
105+43 ⁸³		33447			105+16.63	105+35.63		83.60	10.0	2.05
		.2423				105+00.42				
104+93 ⁷⁶		32380			104+83.76	104+66.96		83.33	10.0	2.357
		.2492			104+47.00	104+30.25	4395.19			
104+43 ⁷²		33822			104+17.00	104+0.25		82.82	10.0	2.10 ⁷
		.2517			103+23.25					
103+93 ⁶⁵		35339						84.23	10.0	1.85
		.1369								
103+66 ⁶²		3408			Ctr. Man hole			84.27		= N. Edge of cross beam

Continued on page 4