

JULY 12 1988
 A@ WITNESS COR

TOWER	D	0-00	11.3	10.5	10.9	10.42
	R	180-00	9.9	10.0	9.95	
EYRIG	D	110-23	41.3	41.0	41.15	34.1
	R	290-23	26.9	27.2	27.05	
	M	110° 23'	23.67"			23.68
TOWER	D	15-00	27.9	28.8	28.35	23.90
	R	195-00	18.0	18.9	18.45	
EYRIG	D	125-23	56.3	56.9	56.6	48.05
	R	305-23	39.4	39.6	39.5	
	M		24.65"			24.65
TOWER	D	30-02	35.4	36.1	35.75	32.52
	R	210-02	29.4	29.0	29.7	37.0
EYRIG	D	140-26	03.4	03.3	03.55	54.52
	R	320-25	46.4	45.0	45.7	01.92
	M		22.22"		22.00"	
TOWER	D	45-00	51.4	51.6	51.5	50.0
	R	225-00	48.4	48.6	48.5	
EYRIG	D	155-24	21.0	20.4	20.7	13.55
	R	335-24	06.4	06.2	06.4	
	M		23.55"			
TOWER	D	60-00	10.2	10.0	10.1	07.65
	R	240-00	09.0	09.4	09.2	10.75
EYRIG	D	170-23	05.0	05.4	05.2	30.85
	R	350-23	38.0	37.8	37.9	37.63
	M		23.6	24.0	23.8	
	M		27.41"		23.20	
TOWER	D	75-00 ²⁵	26.2	26.0	26.1	24.15
	R	255-00	22.3	22.1	22.2	
EYRIG	D	185-23	56.2	55.8	56.0	48.98
	R	05-23	41.8	42.1	41.95	
	M		24.73"			

CONT