

TRAPPER

PORT	D	0° 00'	10.8" ¹⁰ 10.2"	10.50"	9.58"
	R	180° 00'	08.4 08.9	08.65"	
TOWER	D	40° 29'	11.6" 11.6"	11.60"	9.98"
	R	220° 29'	08.1" 08.6"	08.35"	
		m = 40° 29' 00.40"			
MAPLE	D	83° 52'	47.7 48.2	47.95"	47.43"
	R	268 52	46.8 47.0	46.90"	
		m = 83° 52' 37.85"			
PORT	D	15° 00'	24.2" ²⁵ 23.4"	23.80"	23.60"
	R	195° 00'	23.6" 23.2"	23.40	
TOWER	D	55° 29'	24.6" 24.8"	24.70	23.53
	R	235° 29'	22.5" 22.2"	22.35"	
		m = 40° 28' 59.93"			
MAPLE	D	98° 53'	00.8" 00.6"	00.70	58.65"
	R	278° 52'	56.8" 56.4"	56.60"	
		m = 93° 52' 35.05"			
PORT	D	30° 02'	35.1" ³⁵ 35.0"	35.05"	34.23
	R	210° 02'	33.6" 33.2"	33.40	
TOWER	D	70° 31'	34.6" 35.0"	34.80"	34.25"
	R	250° 31'	33.2" 34.2"	33.70"	
		m = 40° 29° 00.02"			
MAPLE	D	113° 56'	11.6" 11.6"	11.60"	11.55"
	R	293° 55'	11.1" 11.9"	11.50"	
		m = 83° 52' 37.82			
PORT	D	45° 00'	52.2" ⁵⁰ 51.7"	51.95"	50.93"
	R	225° 00'	49.8" 50.0"	49.90	
TOWER	D	85° 29'	53.0" 53.0"	53.00	51.75"
	R	265° 29'	50.6" 50.4"	50.50"	
		m = 40° 29' 00.82"			
MAPLE	D	128° 53'	28.0" 28.0"	28.00	26.18"
	R	308° 53'	24.5" 24.2"	24.35"	
		m = 83° 52' 35.25"			